



Green-Safe Technology

Single Component Penetrating Invisible Sealer

DESCRIPTION:

CMP-1000 is a penetrating, colorless surface treatment which produces an invisible protective coating. It can also be used on stone, tile, marble and virtually any concrete substrate.

CMP-1000 also protects from a variety of stains including oil and serves as a water repellent.

PRODUCT FEATURES

- ▶ Penetrates deep into substrate
- ▶ Very easy to apply
- ▶ Breathable
- ▶ Low odor
- ▶ Non-Flammable, Non-Toxic, Non Explosive
- ▶ Water based and VOC compliant
- ▶ No dangerous emissions or irritating fumes

SUBSTRATE PREPARATION:

Substrate must be well-bonded and completely clean; free of oil, wax, grease, sealers, curing compounds, asphalt, gypsum based patch, paint, dirt, loose surface material and any contaminate that will act as a bond-breaker.

APPLICATION PROCEDURES

Apply CMP-1000 liberally using sprayer, roller or brush. Initial coat should be applied at a rate of 200 - 250 sq. ft. per gallon. Allow to dry and apply second coat at a rate of 350 - 400 sq. ft. per gallon. Let coating dry and cure at ambient temperature for 24 to 72 hours to reach maximum protection.

LIMITATIONS:

Do Not use AS-100 as an additive.

09 65 00
Floor Finishes

9

Packaging:

1 Gal. jug : 4 per case : 36 per pallet
5 Gal. pail : 36 pails per pallet

Color: Clear

Shelf Life: 1 Year in original package

Coverage (Yield):

350 - 400 sq. ft. per gallon

Application Temperature Range:

50°F - 90°F

Dry Time:

1 - 2 hours Depending on Conditions

Flammability: (ASTM E84)

Flame Spread: -0-

Fuel Contribution: -0-

Smoke Development: -0-

Clean Up Procedure:

Immediately clean tools with water

Health & Safety:

Please refer to the Material Safety Data Sheet (MSDS) prior to using this product. MSDS sheets are available by calling 215.672.6364 or you can visit www.levelingcements.com.

Manufactured By:

CMP Specialty Products, Inc
PO Box 213
Horsham, Pennsylvania 19044
Phone: 215.672.6364
Fax: 215.672.6384
www.levelingcements.com